



6540 Arlington Boulevard  
Falls Church, VA 22042

Tel: 703-536-7080  
[www.irrigation.org](http://www.irrigation.org)

**Smart Water Application Technology™ (SWAT™) Performance Report**

**Testing Agency: Center for Irrigation Technology** [www.californiawater.org](http://www.californiawater.org)

**Product: Weathermatic SL1600**

**Product Type: Climatologically Based Controller**

**Product Description: Weathermatic SL1600 controller with SLW series on-site weather monitor**

**SWAT™ Protocol\*: Turf and Landscape Equipment Climatologically Based Controllers 7<sup>th</sup> Draft Testing Protocol (November 2006)**

The concept of climatologically controlling irrigation systems has an extensive history of scientific study and documentation. The objective of this protocol is to evaluate how well current commercial technology has integrated the scientific data into a practical system that meets the agronomic needs of turf and landscape plants. The evaluation is accomplished by creating a virtual landscape subjected to a representative climate to evaluate the ability of individual controllers to adequately and efficiently irrigate that landscape. After initial programming and calibration the controller is expected to perform without further intervention during the test period. Performance results indicate to what degree the controller maintained root zone moistures within an acceptable range. If moisture levels are maintained without deficit, it can be assumed the crop growth and quality will be adequate. If moisture levels are maintained without excess it can be assumed that scheduling is efficient.

\*All SWAT™ Protocol may be viewed at [www.irrigation.org](http://www.irrigation.org)

**Weathermatic SL1600 Controller SWAT™ Performance Summary**

Irrigation Adequacy	Irrigation Excess
<b>Minimum of 6 test zones: 100%</b> <b>Maximum of 6 test zones: 100%</b> <b>Mean/Average of 6 test zones: 100%</b> <b>Irrigation Adequacy</b> represents how well irrigation met the needs of the plant material. This reflects the percentage of required water for turf or plant material supplied by rainfall and controller-scheduled irrigations. Research suggests that if this value is between 80% and 100%, the acceptable quality of vegetation will be maintained.	<b>Minimum of 6 test zones: 0%</b> <b>Maximum of 6 test zones: 2.3%</b> <b>Mean/Average of 6 test zones: 0.4%</b> <b>Irrigation Excess</b> represents how much irrigation water was applied beyond the needs of the plant material. This reflects the percentage of water applied in excess of 100% of required water according to data from CIMIS station #80 Fresno State, Fresno County during the test period.

**Product Detail Supplied by Manufacturer**

**Weathermatic SL1600** [www.smartline.com](http://www.smartline.com)

Installation	Data Source	Data Link	Initial Purchase	Additional Hardware	Additional Fees
Replaces existing controller or is installed on a new system.	Weathermatic on-site weather monitor	Direct low voltage wire or wireless	Purchase price is based on number of zones. Weather monitor is an additional cost.	None required	None

**Additional Features**

Zones	Time of Day	Day of Week	Other	If Data Link is Discontinued
Available in 4-8, 4-24, 12- 48 zone models	Capable of restricting the time of day for watering.	Capable of restricting watering days by selection or interval.	<input type="checkbox"/> Built in valve locator feature <input type="checkbox"/> Calculates irrigation schedules based on zone-specific, Irrigation Association recommended parameters including plant, soil, slope, and sprinkler type. <input type="checkbox"/> On-board multi-meter	If weather monitor connection is discontinued it may be used as a standard irrigation controller with water budget and cycle and soak capability.