
Rainwater Harvesting for Landscape



AUSTIN ENERGY GREEN BUILDING PROGRAM Irrigation
Dick Peterson

Environmental

Program

Coordinator

Austin Energy

Green Building Program

www.austinenergy.com

Rainwater Through The Ages

- Rainwater harvesting practiced for over 4,000 years in desert of southern Israel
- Ancient Roman had cisterns and aqueducts
- § Early 1900's farms and ranches had cisterns
- Current resurgence of rainwater collection Lady Bird Johnson Wildflower Center
 - Currently72,000 gallon capacity
 - have plans for another 25,000 gallons
- Many Caribbean nations mandate rainwater harvesting



Why Collect Rainwater?

- Rainwater pH is almost neutral
- Plants love it
- Rainwater does not have dissolved minerals from the soil
- Or chemicals from water treatment plants
- Harvesting reduces erosion
- Reduces water bill you do not use as much expensive potable water on your landscape

First Flush "Poor Man's Roof

Washer"



- PVC pipe with fittings running to the ground with a screw on cap at the bottom for clean out
- First 8-10 gallons collects debris from roof and gutters -- diverted by first flush before tank inlet

First Flush "Poor Man's Roof


Washer"



- PVC pipe with fittings running to the ground with a screw on cap at the bottom for clean out
- First 8-10 gallons collects debris from roof and gutters -- diverted by first flush before tank inlet

First Flush "Poor Man's Roof

Washer"





- PVC pipe with fittings running to the ground with a screw on cap at the bottom for clean out
- First 8-10 gallons collects debris from roof and gutters -- diverted by first flush before tank inlet

PVC Drain-Waste-Vent Fittings


ADAPTER FITTING CLEANOUT SP x FPT (WPLUG)	TEST W/PLUG H x H x FPT		CLOSIET BEND ALL HUB (1/4 BEND)
ALL HUB (⁽⁾ 4 BEND)	SANITARY STREET SP x H x H	Ē1	LONG TURN ALL HUB
90° ELBOW SIDE INLET ALL HUB ('A BEND)	90° ELBOW LOW HEEL INLET ALL HUB (¼ BEND)		PIPE INCREASER ALL HUB
221/2° ELBOW ALL HUB (¹/is BEND)	DOUBLE ALL HUB		CLEANOUT 2-WAY
45° ELBOW ALL HUB (1/6 BEND)			ALL HUB (% BEND)
PVC TRUE UNION THREADED OR SOLVENT			PVC BALL VALVE THREADED

Tanks are available in many sizes






Simple System Diagram






Drinking Water Systems



Drinking water systems require more equipment and maintenance




From "Rainwater-Collection Systems" by Peter Pfeiffer

Fine Homebuilding Magazine

Drinking water systems require more equipment and maintenance



Good source of tanks are "feed and ranch" stores




To reduce algae, tanks should be black, green, covered, or painted




A 10' x 10' garden shed can collect 60 gallons in just a 1" rain



Typical Underground Cistern




37,500 gallon Ferro-cement tank



From "Rainwater-Collection Systems" by Peter Pfeiffer

Fine Homebuilding Magazine



How much will rainwater harvesting cost?

- It really does vary...
 - Do you already have gutters?
 - If not, what type will you install?
 - Type and size of tank
 - Will you use a pump?
 - Pad construction



Roof Type

- Any roof will do
 - Metal is the ideal roof smooth and non-absorbent
 - © Composite, wood shingles, asbestos...all absorb water and will break down over time


S Gutters

• 30 cents per foot for plastic up to \$15 per foot for copper

Screens

Screens are not necessary unless your house has a lot of tree cover


Roof Washer





Roof washers clean the water, not the roof

The first water to fall on the roof cleans away dirt and debris accumulated since the last rain. Commercially available roof washers such as the one shown here funnel the water first through a leaf basket that collects the heaviest debris. The first 35 gal. of water, which is the dirtiest, fills the quiet chamber, where it drains away slowly. Cleaner water then passes through a replaceable filter element.



From "Rainwater-Collection Systems" by Peter Pfeiffer

Fine Homebuilding Magazine

- Roof Washer
 - **\$300-600**
 - scontainer with 30 micron filter
 - Swater must pass through filter before filling tank
 - If not cleaned regularly
 - breeding ground for bacteria
 - will keep water from entering tank
 - not necessary for non-potable systems

Barrels

- Purchased or recycled barrel
- Should be painted to keep out sunlight and prevent algae growth



- Polypropylene Tanks
 - \$\$.35 to \$1.00 per gallon
 - Most common
 - Easy to install
 - Should be black, green or painted



© Concrete or Ferro-cement tanks

\$\$.35 to \$1.00 per gallon



- Metal Tanks
 - §40-60 cents per gallon
 - Short life span rust, except with special liners





- Wooden Tanks
 - \$\$2.00+ per gallon
 - Ideal for remote locations, pack in the pieces
 - Can be dissembled and moved
 - Available up to 2,000,000 gallons!



- Stone Tanks
 - Very expensive
 - Difficult to maintain



- Pumps
 - \$200-600
 - install pump as close to tank as possible
 - protect from freezing
 - in-tank float switch
 - in general 3/4 quarter horsepower is sufficient
 - § It will allow you to pump water 400 feet

Maintenance

- With a first flush system you will want to clean out the PVC after every rainfall
- If you have screens, clean them after a rain when there has not been any rainfall for a period of time
- Most people who have installed their systems over the past 5 years, have not had to clean the tank of debris

Bt-Biological Mosquito Control



Whisky is for drinkin'...



Mark Twain


Water is a precious resource...

Use it wisely...

Harvest rainwater!

Austin History Center, St. Edward's cadet straddling Lake Austin

Rainwater Harvesting for Landscape



AUSTIN ENERGY GREEN BUILDING PROGRAM Irrigation
Dick Peterson

Environmental

Program

Coordinator

Austin Energy

Green Building Program

www.austinenergy.com